

MEDIA CONTROL VALVE

This patent application is a continuation-in-part application and claims priority to U.S. Serial No. 09/709,894, filed November 10, 2000 and entitled MEDIA CONTROL VALVE.

Background

1. Field of the Invention

The present invention is related to media control and, more specifically, media control valves used to control the flow of a media into a fluid stream as part of an apparatus for treatment of a surface.

2. Description of the Related Art

A typical media control valve is disclosed in U.S. Patent No. 3,476,440 ("the '440 patent"), which is hereby incorporated by reference in its entirety. The valve of the '440 patent is attached to a media vessel and controls the flow of the media from the media vessel into a conduit containing a fluid stream. This conduit terminates in a nozzle. Fluid and media pass through the nozzle at high speed and are typically used to treat surfaces.

Other uses for media control valves have been proposed. For example, U.S. Patent No. 5,810,045 ("the '045 patent") discloses a valve for introducing particulate materials into a high-pressure air stream and suggests several uses for this valve. For example, the '045 patent suggests that the valve may be used for purposes such as introducing fluid catalytic cracking catalyst particles into fluid catalytic cracking units used to crack and reform various petroleum based products, introducing particulate catalysts into other kinds of chemical processes, and spraying particulate ingredients on adhesive substrates as part of various manufacturing processes.

Various improvements to the basic media control valve have been proposed. For example, U.S. Patent Nos. 5,407,379 ("the '379 patent") and 5,401,205 ("the '205 patent") disclose a media control valve having a media passage between the media control valve and the conduit. The media passage converges into a slot-shaped outlet in the conduit so as to reduce the perimeter of the outlet placed perpendicular to air flow and consequently reduce turbulence as air passes across the outlet. The media control valve disclosed in the '205 and '379 patents is particularly useful in metering and dispensing sodium bicarbonate media.

The '045 patent, discussed previously, also discloses a modification of the original media control valve, including the use of multiple seals around a plunger of the valve with an exhaust therebetween to remove any contaminants that breach the seals.

Summary

According to one embodiment of the present invention, a media control valve is provided including a valve body having a media inlet and a media outlet, and a plunger and sleeve positioned within the valve body. The media control valve also includes a media opening in the sleeve having a first portion proximate to the media outlet and a second portion distal to the media outlet, wherein the second portion is broader than the first portion. The media control valve further includes a housing connected to the valve body, a piston positioned within the housing and connected to the plunger, and a base connected to the valve body in communication with the media outlet.

According to another embodiment of the present invention, a valve is provided including a body having an opening and an outlet. The opening in the outlet includes a first portion proximate to the outlet and a second portion distal to the outlet, wherein the second portion is broader than the first portion. The valve further includes a closing member positioned within the body so as to selectively cover the opening.

According to another embodiment of the present invention, a valve is provided including a body and a closing member positioned within the body. The valve also includes a housing and a piston within the housing. The piston is connected to the closing member and has a contaminant isolation region.

According to another embodiment of the present invention, a media control valve is provided including a valve body having a media inlet and a media outlet, and a plunger and sleeve positioned within the valve body. The media control valve also includes a media opening in the sleeve, a housing connected to the valve body, a piston having a contaminant isolation region positioned within the housing and connected to the plunger and a base connected to the valve body in communication with the media outlet.

According to another embodiment of the present invention, a media control system is provided including a media vessel, an air flow path, a media flow path, and a media control valve positioned on the media flow path. The media flow path has a substantially linear axis and includes a media inlet connected to the media vessel and a media outlet connected to the media flow path.

According to another embodiment of the present invention, a media control valve is provided including a valve body comprising a media inlet and a media outlet, and means for providing a gentle seal positioned within the valve body. The valve also includes a sleeve positioned within the valve body, a media opening in the sleeve, a housing connected to the valve body, and a base connected to the valve body and in communication with the media outlet.

Brief Description Of Drawings

The foregoing and other advantages of the present invention will be more fully appreciated with reference to the following drawings in which:

FIG. 1 is a diagram of a blasting system incorporating the media control valve of the present invention;

FIG. 2 is a cross-sectional side view of a media control valve according to an aspect of the present invention;

FIG. 3 is an exploded, elevational view of the valve shown in FIG. 2;

FIG. 4 is a side elevational view of a sleeve according to one embodiment of the present invention;

FIG. 5 is an illustration of example embodiments of a media opening according to the present invention;

FIG. 6 is a perspective view of the sleeve illustrated in FIG. 4 with phantom lines to show relative thickness;

FIG. 7 is a bottom plan view of the sleeve illustrated in FIG. 4 with phantom lines to show relative thickness;

FIG. 8 is a cross-sectional side view of the sleeve illustrated in FIG. 4, taken along section line 8-8 of FIG. 7;

FIG. 9 is a top plan view of a plunger according to one embodiment of the present invention;

FIG. 10 is a cross-sectional side view of the plunger illustrated in FIG. 9, taken along section line 10-10 of FIG. 9;

FIG. 11 is a cross-sectional side view of a media control valve according to an aspect of the present invention;

FIG. 12 is an exploded, elevational view of the valve shown in FIG. 11; and

FIG. 13 is a partial side view of one aspect of the present invention.

Detailed Description

The present invention is directed to a valve for controlling the flow of a media to a fluid stream, referred to herein as a media control valve. By media, it is meant any material or materials that may be desired to be added to another material or materials. While various
5 solid, fine particulate, blasting media, such as sand, metal shot, and the like, are used by way of example herein, the media that may be supplied by the media control valve of the present invention is not so limited, and may include a wide variety of materials including liquids and gasses as well as solid particles.

In one embodiment, the media control valve of the present invention includes a
10 valve body having a media inlet and a media outlet. A housing is connected to the valve body. A plunger is positioned within the valve body and is connected to a piston positioned within the housing. A base is connected to the valve body such that it communicates with the media outlet. The media control valve of this embodiment may further include a sleeve disposed between the valve body and the plunger. This sleeve may contain a media
15 opening. In some embodiments of the media control valve of the present invention, the media opening has a first portion proximate to the media outlet and a second portion distal to the media outlet, the second portion being broader than the first portion. In other embodiments of the invention, the piston includes a contaminant isolation region. These and other specific embodiments of the invention will now be described with reference to the
20 Figures.

FIG. 1 illustrates a typical system in which the media control valve of the present invention may be employed. In FIG. 1, a media control valve 10 is part of a blast system
25 150 used to treat a surface by projecting a media 140 at the surface. Media 140 typically consists of solid particles, such as sand, shot, nut shells, sodium bicarbonate, other abrasives, and the like depending on the surface being treated and the materials(s) being removed from the surface. Blast system 150 includes a fluid supply 100 which supplies a fluid stream through conduit 110. Typically, the fluid employed is air, though any readily available, relatively inert carrier fluid may be employed. Media 140 may be stored in a media vessel 130 and supplied to the fluid stream within conduit 110 through actuation of
30 media control valve 10. The fluid stream and entrained media 140 then pass through conduit 110 to a nozzle 120 where they are directed at a surface to be treated.

Referring now to FIGS. 2 and 3, in one embodiment media control valve 10 may include a valve body 20 having a media inlet 22 and a media outlet 24. A plunger 30 is

positioned within valve body 20 and a sleeve 32 is positioned between valve body 20 and plunger 30. Sleeve 32 may include a media opening 34 that allows media to pass from media inlet 22 to media outlet 24 when plunger 30 is not blocking such flow. In this embodiment, media control valve 10 further includes a housing 40 that is connected to valve body 20. A piston 42 is connected to plunger 30 and positioned within housing 40. A base 60 is connected to valve body 20 such that it communicates with media outlet 24.

Valve body 20 may be constructed in any manner and of any materials that provide valve body 20 the desired configuration and durability. For example, valve body 20 may be constructed with media inlet 22. Media inlet 22 may be constructed in any manner that allows it to receive media. For example, media inlet 22 may be constructed to connect to a media vessel. When media inlet 22 is constructed to connect with a media vessel, it may be constructed to connect in any manner that provides a secure connection and allows media to flow into valve body 20 from the media vessel. For example, media inlet 22 may be threaded, or otherwise provided with a fitting such that it may mate with a connector attached to the media vessel.

Valve body 20 may also be constructed with media outlet 24. Media outlet 24 may be constructed in any manner that allows media to pass from valve body 20 into a fluid passage 62 within base 60. For example, media outlet 24 may be an aperture of any size and shape capable of delivering media in an adequate volumetric flow through a conduit, and, most typically, to a blast nozzle. In preferred embodiments, media outlet 24 may be shaped as a circular hole.

Valve body 20 may also be constructed to house plunger 30. Valve body 20 may include an open area having a shape corresponding to plunger 30. Valve body 20 may also be constructed to allow sleeve 32, seals 36 or seat 26 to reside within valve body 20. For example, the opening in valve body 20 for receiving plunger 30 may be large enough to also accommodate sleeve 32 or seals 36 between plunger 30 and valve body 20. Similarly, valve body 20 may include a portion shaped to accommodate seat 26, typically adjacent to media outlet 24.

Valve body 20 may also be constructed with a mechanism for allowing the media to pass out of the media vessel without passing into the conduit. For example, valve body 20 may include a bypass or cleanout 28. Cleanout 28 may be constructed in any manner which allows the media to flow out of the media vessel without entering the conduit. For example, cleanout 28 may include an opening in valve body 20 communicating directly with media

inlet 22. Typically during operation of media control valve 10, cleanout 28 is closed. Cleanout 28 may also include an opening onto which a cover may be mated when it is desired to close cleanout 28.

Valve body 20 may be constructed of any material or materials that have sufficient durability for valve body 20 and are compatible with media and other materials which may come in contact with valve body 20. For example, valve body 20 may be constructed of various metals and metal alloys. Preferably, valve body 20 is constructed of an aluminum alloy because of its relatively low weight and cost and relatively high strength and abrasion resistance. Preferably, the aluminum alloy has a hard-coat anodized finish to improve its abrasion resistance. In one embodiment, valve body 20 is constructed of 356 T6 aluminum alloy with a hard-coat anodized finish.

Valve body 20 may be constructed by any method capable of producing valve 20 from a desired material or materials of construction. For example, where valve body 20 is constructed of certain metals, valve body 20 may be cast, machined or both. Preferably, valve body 20 is constructed by casting, and, more preferably, investment casting, because casting is relatively inexpensive and produces a relatively high quality product having sufficient dimensional stability.

Referring now also to FIGS. 9 and 10, plunger 30 may be constructed in any manner and using any materials resulting in plunger 30 having the shape and durability to selectively prevent flow of media through valve body 20. For example, plunger 30 may be constructed in any shape that may mate with valve body 20, sleeve 32 and seals 36 to selectively prevent flow of media from media inlet 22 to media outlet 24. In order to selectively prevent flow of media, plunger 30 is typically constructed such that it may move within valve body 20, selectively exposing a media opening 34 in sleeve 32 and allowing the media to flow from media inlet 22 to media outlet 24. Preferably, plunger 30 is cylindrical and of uniform cross-section.

Plunger 30 may be constructed to mate with piston 42. For example, plunger 30 may be threaded at one end, such that it may be mated to piston 42 with a threaded nut 70. Alternatively, plunger 30 may thread directly into piston 42 or be connected with another connector known to those of skill in the art.

Plunger 30 may be constructed of any material or materials that are sufficiently durable and inert to selectively prevent the passage of media through or past plunger 30 and to provide long life of plunger 30. For example, plunger 30 may be constructed of the same

material or materials as valve body 20. However, as plunger 30 may be subject to more wear than valve body 20, it is preferred to construct plunger 30 of a more durable material than valve body 20. For example, plunger 30 may be constructed of steel, such as 304 stainless steel, with harder material, such as tungsten carbide, on the outer, lower portion 31 of plunger 30. These materials are selected due to their relatively high strength and dimensional stability. Plunger 30 may be made by any conventional method to produce the desired shape from the material or materials of construction. For example, plunger 30 may be constructed by the same method as valve body 20.

Referring now also to FIGS. 4-8, Sleeve 32 may be constructed in any manner and of any materials to produce a desired configuration to be contained within valve body 20 and to mate with plunger 30. For example, sleeve 32 may be constructed as a cylindrical annulus where plunger 30 is cylindrical and valve body 20 contains a cylindrical opening therein. Sleeve 32 may be constructed with a media opening 34 to control the flow of media from media inlet 22 to media outlet 24. Media opening 34 may be constructed in any shape that controls the flow of media 140 from media inlet 22 to media outlet 24 as desired when valve 10 is open. For example, as illustrated in FIG. 5, media opening 34 may be irregularly shaped, or, more conventional, with a circular, elliptical, or other geometric shaped opening; alternatively it may only include a narrow opening. Preferably, as illustrated in FIGS. 4 and 6, media opening 34 includes a first portion 200 proximate to media outlet 24 and a second portion 202 distal to media outlet 24, second portion 202 being broader than first portion 200. This embodiment of media opening 34 facilitates metering particulate media when media valve 10 is in a partially open position.

In some embodiments, the flow control function of media opening 34 in sleeve 32 may be constructed directly into valve body 20. For example, valve body 20 may be constructed in a manner which is equivalent to sleeve 32 being fused to valve body 20. However, it is preferable to have a separate sleeve 32 because this allows relatively straightforward modification of media opening 34, and, thus, the flow properties of media control valve 10, and because sleeve 32 may be subject to wear and may need periodic replacement.

Sleeve 32 may be formed out of any material that may be shaped as desired and provides sufficient durability. For example, sleeve 32 may be formed of a material that may maintain the shape of media opening 34 despite the passage of media 140 through media opening 34 over time. In some embodiments, sleeve 32 may be constructed of a metal,

metal alloy or polymer. Preferably, sleeve 32, like plunger 30, is constructed of steel with tungsten carbide on the surfaces subject to the most wear, such as the inner, lower portion 35 of sleeve 32. Again, these materials are selected due to their abrasion resistance and dimensional stability. However, it should be understood that the preferred material of construction for sleeve 32 may vary with the media used and, in other embodiments, other materials may be preferred. For example, in some embodiments, it is preferred to form sleeve 32 from urethane because of its cost, serviceability and resistance to jamming with certain media, such as steel shot. Sleeve 32 may be constructed by any method that produces sleeve 32 having the desired shape and durability out of the material or materials of construction. For example, sleeve 32 may be constructed by sintering, casting or molding and polymerization of a prepolymer.

One or more seals 36 may be positioned between plunger 30 and valve body 20 to prevent media, fluid from the conduit or other contaminants from passing between valve body 20 and housing 40. In a preferred embodiment, three seals 36 are positioned between plunger 30 and valve body 20 to prevent contamination. Typically, the likelihood of contamination is much greater from valve body 20 to housing 40 than the reverse. Accordingly, seals 36 are typically oriented to face valve body 20. In some instances, such as where the pressure within housing 40 may exceed the pressure within valve body 20, one or more of seals 36 may be oriented to face housing 40. In such instances, it is preferred that seals 36 closest to housing 40 be faced toward housing 40. In one embodiment, several seals 36 are formed as a unitary structure. For example, three seals may be formed as a single solid piece of material.

Seals 36 may be formed out of any material that will provide an adequate seal with sufficient durability. For example, seals 36 may be formed of a resilient, pliable material, such as some polymers. The material may also be abrasion resistant and have a low coefficient of friction. In some instances, seals 36 may be constructed of an elastomer. Preferably, seals 36 are constructed of molythane because it is self-lubricating or urethane because of its abrasion resistance. Seals 36 may be constructed by any method that produces seals 36 having the desired seal and durability out of the material or materials of construction. For example, seals 36 may be constructed by molding and polymerization of a prepolymer.

Seat 26 may be constructed of any material or materials and in any manner that produces a solid connection with plunger 30 when media control valve 10 is in a closed

position. For example, seat 26 may be constructed to fit snugly with plunger 30. In embodiments where plunger 30 is cylindrical, seat 26 may be a circular annulus. Seat 26 may be constructed of the same materials and using the same methods as seals 36. Seat 26 may also be constructed of less resilient materials than would typically be used for seals 36 and may even be formed of the same material as valve body 20.

Housing 40 may be constructed in any manner and of any material or materials that produce housing 40 that may be connected to valve body 20, house piston 42 and have sufficient durability. For example, housing 40 may be constructed to function as a cylinder for piston 42. Preferably, the inside of housing 40 is a uniform circular cylinder, however, this is not required as long as the inside of housing 40 connects with piston 42 to provide a seal. Housing 40 may be constructed such that piston 42 may travel within housing 40. Preferably piston 42 has sufficient range of motion to allow plunger 30 to move from a fully open position in which plunger 30 does not obstruct media opening 34 to a fully closed position in which plunger 30 rests against valve seat 26, completely obstructing flow through media opening 34. Piston 42 may effectively divide housing 40 into a drive chamber 44 and an exhaust chamber 46. Where housing 40 has a drive chamber 44, housing 40 may be constructed with a drive inlet 48 to drive chamber 44, allowing pressure to be applied to piston 42 to open media control valve 10.

Housing 40 may also include one or more vents 50 in exhaust chamber 46, allowing fluid to flow into and out of exhaust chamber 46 as the volume within exhaust chamber 46 varies with the motion of piston 42. Vents 50 may include filters 52 to prevent contaminants from entering housing 40 while still allowing vents 50 to perform their exhaust function. Preferably, filters 52 in vents 50 are capable of filtering particles larger than about 20 microns as this filters most particles, but does not restrict the flow of fluid through vents 50 enough to significantly affect performance of media control valve 10. Furthermore, particles less than about 20 microns may be able to fit between housing 40 and piston 42 and are less likely to damage piston 42 or cause piston seal 58 to fail. A suitable filter 52 may be constructed by sintering an appropriate material, such as a metal or metal alloy. Preferably the filter is constructed of sintered brass.

Housing 40 may be constructed to provide access to the inside of housing 40. For example, housing 40 may include a cap 66, which may be removed to provide access to the inside of housing 40. Cap 66 may be constructed in any manner that allows it to connect securely with housing 40 yet allows access to the inside of housing 40. For example, cap 66

may be constructed to cover the open top of housing 40, and may include structure allowing it to be connected to housing 40. In one embodiment, cap 66 and housing 40 may include matching holes, through which bolts 68 may be inserted to secure cap 66 to housing 40. Preferably, in order to insure a secure connection, four evenly spaced bolt holes 64 and bolts 68 are used to secure cap 66 to housing 40. Cap 66 may be constructed of the same materials and by the same method as housing 40.

Housing 40 may also be constructed to include structure to allow the adjustment of the operation of media valve 10. For example, housing 40 may enclose a spring 56 and attendant structure to adjust the tension on spring 56 and, thus, the operation of media control valve 10. Alternatively, housing 40 may include an air shock (not shown) and attendant structure. In one embodiment, spring 56 rests between piston 42 and cap 66, biasing piston 42 and plunger 30 toward media outlet 24 and thus biasing media control valve 10 into a closed position. The tension on spring 56 may be used to control how difficult it is to move piston 42, and thus, the amount of pressure required to actuate media control valve 10 or the degree of actuation for a given pressure. Structure to adjust the tension on spring 56 may include a spring retainer 80 that mates with housing 40. Where spring retainer 80 is used to allow the tension on spring 56 to be adjusted, a device for facilitating the adjustment of spring retainer 80, such as a knob 82, crank or other handle, may be used. An O-ring 84, or like seal, may be positioned between spring retainer 80 and housing 40, to prevent the ingress of contaminants into housing 40. Media control valve 10 may include a metering indicator. For example, spring retainer 80 may include marking corresponding to the degree to which media control valve 10 is open.

Housing 40 may be constructed of any material or materials that may be shaped in the desired configuration and has sufficient durability to provide long life. For example, housing 40 may be constructed of the same materials as valve body 20. Similarly, housing 40 may be constructed using the methods discussed with respect to valve body 20.

Piston 42 may be constructed in any manner and using any materials that allow it to fit snugly within housing 40 and to connect with plunger 30 such that plunger 30 is moved with the motion of piston 42. For example, piston 42 may be relatively flat and shaped to match the cross-section of housing 40. Typically, piston 42 will be circular to match the circular cross-section of cylindrical housing 40. Piston 42 may be constructed with structure to connect it to plunger 30. For example, where plunger 30 includes a threaded

region, piston 42 may have a hole therein through which a portion of plunger 30 is inserted, and nut 70 threaded onto, to attach piston 42 to plunger 30.

Piston 42 may be constructed with structure to insure that fluid, media, contaminants and other materials are prevented from passing between drive chamber 44 and exhaust chamber 46 of housing 40. For example, piston 42 may be constructed with one or more retainers adapted to maintain a piston seal 58 in place around piston 42.

Piston 42 may be constructed to reduce the adverse effect of media and other contaminants that find their way into drive chamber 44. For example, piston 42 may include a contaminant isolation region 48 where contaminants are collected and isolated from more sensitive areas of media control valve 40, such as the walls of housing 40 and piston seal 58. In one embodiment, contaminant isolation region 48 includes a recess in piston 42. In this embodiment, piston 42 may have an overall dish shape, allowing contaminants to settle into the dish.

Piston 42 may be constructed of any material or materials that provide sufficient rigidity and durability. For example, piston 42 may be constructed of a metal, metal alloy or polymer. Preferably, piston 42 is constructed of aluminum because of its relatively high strength and relatively low cost and weight. More preferably, piston 42 is constructed of 356 T6 aluminum. Piston 42 may be hard-coat anodized. Piston 42 may be constructed by any method that produces piston 42 from the desired material or materials of construction, such as casting, machining or molding.

In some embodiments, structure to prevent piston 42 from impacting against housing 40 or cap 66 may be included in media control valve 10. For example, structure may be positioned within housing 40 to absorb the impact of piston 42 striking housing 40 or cap 66. In one embodiment, this structure may comprise a bumper, such as bump ring 86, capable of absorbing the impact of piston 42 striking it. Bump ring 86 may be constructed in any manner and of any material or materials that allow it to intercept piston 42 and to dissipate some of its impact energy. For example, bump ring 86 may be constructed as an elastomeric ring and made by a method suitable to the material. Preferably, bump ring 86 is constructed from neoprene because of its impact absorbing ability.

While a conventional piston is described by way of example herein, it should be understood that piston 42 may also be constructed as a diaphragm. Where piston 42 is constructed as a diaphragm, it may be constructed such that it is connected at its edges to housing 40, but is free to move in a central portion connected to plunger 30. For example,

piston 42 may be constructed of a flexible material, which may be an elastomer. Such material may be selected based on its degree of flexibility and its ability to withstand repeated flexing over an extended period of operation of media control valve 10.

In some instances, media control valve 10 may be subject to significant vibration, for example, due to a mechanical agitator operated to improve media flow. Vibration is undesirable because it may, for example, result in a change in metering position. Accordingly, it may be desired to add structure to media control valve 10 that dampens vibration. For example, a structure capable of absorbing vibrational energy or adding friction to prevent parts from vibrating apart may be included in media control valve 10. In one embodiment, a vibration disc 88 is positioned between spring 56 and spring retainer 80 to create friction and prevent slipping of spring retainer 80, potentially resulting in a loss of metering position. Vibration disc 88 may be constructed in any manner and of any material or materials that allow it create friction between two parts. However, vibration disc 88 should not create so much friction that it prevents adjustment or detachment of the parts. For example, vibration disc 88 may be circular, polygonal or of any other shape and may be formed of any material having a relatively high coefficient of friction. Typically, vibration disc 88 is formed of a polymeric material. Preferably, vibration disc 88 is constructed of polyurethane because it may create friction without preventing adjustment.

Base 60 may be constructed in any manner and of any materials that allow communication between media outlet 24 and fluid passage 62. For example, base 60 may be adapted to be attached to valve body 20 and conduit 110, such that fluid passage 62 is in communication with both media outlet 24 and conduit 110. Typically, an opening in base 60 is placed in communication with media outlet 24, allowing media to pass into fluid passage 62. Where base 60 is in communication with media outlet 24, it is preferred that the opening between base 60 and media outlet 24 not impede the flow of media into fluid passage 62 or the ability of plunger 30 to close media control valve 10. For example, the opening between media outlet 24 and gas passage 62 may be larger than media opening 34 in sleeve 32, ensuring that it is not the flow-limiting restriction and allowing media to disperse, making it easier for plunger 30 to move the media aside as it closes.

Base 60 may be constructed with structure allowing it to be connected to valve body 20. The structure allowing base 60 to be attached to valve body 20 may be integrally formed with base 60, allowing base 60 to be unitary structure. This embodiment is in contrast to typical media control valve bases wherein the base consists of several pieces,

such as a separate fluid passage 62 and attachment structure for attaching fluid passage 62 to valve body 20.

In one embodiment, base 60 may include bolt holes 64 through which bolts 68 may be passed to connect base 60 to valve body 20. Preferably, bolt holes 64 extend not only through base 60 but also through valve body 20 and into housing 40. Where bolt holes 64 extend through base 60 and valve body 20 into housing 40, removing bolts 68 allows media control valve 10 to be quickly disassembled for inspection, modification or maintenance. For example, bolts 68 may be removed to allow access to and replacement of sleeve 32, such that sleeve 32 may be replaced with an alternate sleeve 32 having a different media opening 34. As another example, bolts 68 may be removed to provide access to seals 36 for routine maintenance and repair. Preferably, base 60, valve body 20 and housing 40 each include four corresponding bolt holes evenly distributed about such structures to provide a secure connection therebetween. Housing 40 and valve body 20 may include further mating structure that facilitates the attachment of housing 40 and body 20. For example, one of housing 40 and valve body 20 may include a grove 38 or protrusion 54 that mates with a corresponding groove 38 or protrusion 54 in the other one of housing 40 and valve body 20.

Base 60 may be constructed of any material that may be shaped in the desired configuration and has sufficient durability to provide long life. For example, base 40 may be constructed of various metals or metal alloys. In a preferred embodiment, base 60 is constructed of carbon steel, such as 4140 carbon steel, because of its strength, cost, and ability to be hardened and cast. Where base 60 is constructed of carbon steel, it may be heat treated, for example, to approximately 55 Rockwell C, and may be phosphate coated to inhibit rusting. Base 40 may be constructed using the methods discussed with respect to valve body 20.

In some embodiments, fluid passage 62 may be subject to mechanical or chemical damage. Accordingly, structure may be added to fluid passage 62 to resist such damage. For example, a flow sleeve (not shown) may be positioned within fluid passage 62. The flow sleeve may be constructed of any material that is sufficiently chemically and/or mechanically resistant. For example, the flow sleeve may be constructed of polyurethane by conventional techniques.

An alternate embodiment of a media control valve 10 of the present invention is illustrated in FIGS. 11-12. This embodiment serves as an example of another of the variety

of valve structures within the scope of the present invention and illustrates other features that may be incorporated into the media control valves of the present invention.

One common wear point in conventional valves is seat 26. Traditional plungers have sharp edges where the side of the plunger meets the end of the plunger (typically at right angles). It has been discovered that this sharp edge leads to the degradation of the valve seat. Accordingly, one embodiment of media control valve 10 provides a gentle seal. By gentle seal, it is meant a seal in which there are no sharp edges forced against the seat when the valve is closed. Such an embodiment is illustrated in FIGS. 11 and 12.

In one embodiment, a gentle seal may be provided by any structure on plunger 30 or seat 26 that does not provide a hard or sharp edge abutting seat 26. For example, the end of plunger 30 may be rounded or beveled, or may include a rounded or beveled structure attached thereto. In one embodiment, the entire end of plunger 30 is beveled or rounded. In another embodiment, just the edges of plunger 30 are rounded or beveled. As illustrated in FIG. 13, where plunger 30 is beveled, the bevel angle 100 may be less than about 60 degrees with respect to a plane 98 defined by the end of plunger 30. In other embodiments, bevel angle 100 may be less than about 45 degrees, less than about 30 degrees, or less than about 15 degrees.

Where a gentle seal is provided, seat 26 may be as described previously and is preferably a flexible material, such as polyurethane, which may improve the seal. Seat 26 may also be constructed to facilitate formation of a gentle seal. For example, seat 26 may be shaped to mate with plunger 30, having a curved or beveled edge at its opening, or the like.

Conventional media control valves, and even the valve of the embodiment of the invention illustrated in FIGS. 2 and 3, include a media flow path that causes media to change direction and thus impact against it as it passes through the path. By media flow path, it is meant a path between media inlet 22 and media outlet 24 through which media passes when valve 10 is open. It has now been recognized that because of the impact between the media and the media flow path, the media flow path may be degraded. Furthermore, the flow of media may be slowed and impeded by the contact. Accordingly, in one embodiment, the present invention is directed to a media control valve 10 having a flow path 92 designed to reduce impact with the media. For example, as illustrated in FIG. 11, flow path 92 may have a substantially linear axis 96. Media flow path 92 having substantially linear axis 96 may be free of bends, crooks, and the like, such that media may

flow directly from media vessel 130 into fluid path 62 with little or no contact with media flow path 92. Reduction of contact between media flow path 92 and the media may be facilitated by orienting media flow path 92 substantially perpendicularly with respect to the surface upon which the media control system rests. However, such an arrangement is not required, particularly where the flow of media is primarily due to a pressure differential rather than to gravitational forces. Media flow path 92 may be oriented substantially perpendicularly with respect to fluid path 62, which, in most embodiments, will be an air flow path. It should be appreciated that some contact between media flow path 92 and the media is largely unavoidable. For example, contact may occur because of scattering of the media or narrowing of media flow path 92. Nonetheless, to the extent that impact is reduced by straightening of media flow path 92, such an arrangement is within the scope of the present invention.

To facilitate alignment of sleeve 32 such that media opening 34 is properly oriented, structure may be included on sleeve 32 and/or valve body 20. For example, a mating structure such as a ridge and groove, pin and hole, or the like, may be used to facilitate proper alignment. In the embodiment illustrated in FIGS. 11 and 12, a separate sleeve pin 90 is designed to mate with corresponding holes in valve body 20 and sleeve 32.

The illustrative embodiment of FIGS. 11 and 12 demonstrates that media control valve 10 according to the present invention may be constructed relatively simply and, where desired, may be of small size. Such an embodiment may be preferred, for example, in applications where a small, simple valve may be desired to decrease cost or to increase portability. To make media control valve 10 smaller, simpler and less expensive, it may be constructed as an on-off valve, meaning that it has only fully open and fully closed positions. In such an on-off valve, flow control may be accomplished by changing the size of media opening 34 or the pressure differential across the valve. In addition to the improvements already noted, this embodiment includes a plunger 30 capable of also functioning as a piston in housing 40, lowering cost and improving serviceability. This embodiment, as any embodiment of the present invention, may be constructed of the materials and in the manner previously described herein.

It should be appreciated that the features of the embodiment of the invention illustrated in FIGS. 11 and 12 and the embodiment illustrated in FIGS. 2 and 3 are interchangeable and may be combined or interchanged with other features of conventional media control valves. For example, the use of a media opening 34 having a narrower and a

broader portion may be accommodated in the embodiment illustrated in FIGS. 11 and 12. Similarly, the use of a media flow path 92 having a substantially linear axis 96 may be desirable in the embodiment illustrated in FIGS. 2 and 3.

Having thus described certain embodiments of the present invention, various
5 alterations, modifications and improvements will be apparent to those of ordinary skill in the art. Such alterations, variations and improvements are intended to be within the spirit and scope of the present invention. Accordingly, the foregoing description is by way of example and is not intended to be limiting. The present invention is limited only as defined in the following claims and the equivalents thereto.

10 What is claimed is:

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
22